

COOLING FAN

San Ace



2019

SANYO DENKI

San Ace Recommendations Featuring New Products

NEW

DC Splash Proof Fan 9WL type

The series lineup of the Splash Proof Fan has been expanded.

Its IP68-rated water and dust protection ensures stable fan operation even in harsh environments. It offers ideal cooling solutions for PV inverters, rapid EV charging stations, and digital signage.



92×92×38 mm
pp. 299 to 301



140×140×38 mm
pp. 313 to 317



140×140×51 mm
pp. 318 to 321

NEW

DC Long Life Fan 9LG type, 9CRLA type

The series lineup of the Long Life Fan has been expanded.

It offers ideal cooling solutions for communications equipment, industrial inverters, fuel cells, digital signage, servers, and routers.



60×60×76 mm
pp. 373 to 374



140×140×38 mm
pp. 398 to 402



140×140×51 mm
pp. 403 to 406

DC Low Power Consumption Fan 9GA type

The series lineup has been expanded with a new model featuring even lower power consumption than our current model*. It is suitable for use in medical equipment, electrical measuring instruments, PV inverters, industrial inverters, LCDs, and arcade amusement machines.

* 120×120×25 mm San Ace 120 9GV type.

120×120×25 mm
pp. 166 to 169



DC Counter Rotating Fan 9CRH type

The series lineup has been enriched with a new model featuring higher static pressure than our current model*. It offers ideal cooling solutions for servers, power supplies, ICT devices, and data storage systems.

* 40×40×56 mm San Ace 40 9CRV type.

40×40×56 mm
pp. 229 to 230



A wide variety of products are available in various features. See the following pages to find out more.

NEW

DC Splash Proof Centrifugal Fan 9W2T type

The series lineup of the Splash Proof Centrifugal Fan has been expanded. Its IP56-rated water and dust protection ensures stable fan operation even in harsh environments.

It is suitable for outdoor ICT equipment, PV inverters, commercial refrigerators, air conditioning equipment, and dust collectors.



Ø175×69 mm
pp. 336 to 337

DC Centrifugal Fan 9T type, 9B1T type

Centrifugal fans blow air in a centrifugal course. It is suitable for use in ICT equipment, large-scale inverters, refrigeration units, dust collectors, and air conditioners. A Centrifugal Fan has been integrated with an inlet nozzle and brackets into a Bracket-mounted Centrifugal Fan, making the installation work to your device easy.



Ø175×69 mm
pp. 438 to 442



Bracket-mounted Centrifugal Fan
270×270×99 mm pp. 448 to 450

AC ACDC Fan 9AD type

This fan operates by internally converting AC power into DC power. It provides the superior performance of a DC fan with the flexibility of AC input.



92×92×38 mm
pp. 476 to 478



120×120×38 mm
pp. 479 to 481

Airflow Tester pp. 524 to 529

This is a portable measuring device that enables you to easily measure the system impedance and operating airflow of devices.



With connection duct mounted

PWM Controller pp. 518 to 523

This device provides external speed control of PWM control function fans. By using this product, PWM control function fans can be fully utilized without the need for preparing new circuits, contributing to reducing the system power consumption and the fan noise.



Box type



PCB type